



ER ELECTRIC WHEEL LOADER

EREL06



600 kg
Rated loading



1930mm
Max. Dumping Height



40°
Max. Turning Angle



3500*1200*2270mm
Overall Dimensions



- Original electric controller from USA Curtis brand, Quality No 1 and free warranty all over the world.
- Four wheel drive double driving AC motor. Double gearbox. Strong performance on bad road.
- Lead acid battery or Lithium battery both available for customer special working situations.
- The power by full electric, so it could be used in everywhere also without any limit of emission rules.
- Very narrow aisle turning radius.
- Three way or four way or five way multifunctional hydraulic lines for different attachments.
- Agri tyre or normal tyre available for customer.
- Low height which can across most warehouse.

SPECIFICATIONS:

Technical parameters	Overall Weight	1930kg
	Rated Load	600kg
	Overall Size with Bucket(L*W*H)	3500*1200*2270mm
	Overall Size without Bucket(L*W*H)	2450*1200*2270mm
Main performance parameters	Wheel Base	835mm
	Tread Base	1310mm
	Max. Dumping Height	1930mm
	Max. Dump Distance	850mm
	Max. Discharging Angle	40°
	Max. Turning Angle	40°
	Seat Height	1200mm
	Min. Ground Clearance	1600mm
	Min Turning Radius	2300mm
	Time in Total	8s
Motor/Battery	Moving Motor	8kw
	Lifting Motor	6.5kw
	Battery Capacity	48V/300Ah
Tire	Standard Tire	23*8.5 -12
Drive Type	Drive Type	4 wheel drive
Working Time	Working Time	8-9 Hours

